




Maßblatt Drehstrommotor / dimensions three phase motor IM B14 [mm]

Typ	AC	ØD	DB	E	F	HA	PM	L	ØM	ØN	ØP	ØS
MX3 132M-8	257	38	M12	80	10	191	M25*1.5	506	165	130	200	4

technische Daten / technical data

Typ / type	MX3 132M-8	
Leistung / power	[kW]	3,00
Drehzahl / speed	[upm]	720
Anzahl der Pole/ number of poles		8
Nennstrom / rated current (400V)	[A]	7,10
Leistungsfaktor / power factor	[cos φ]	0,73
Wirkungsgrad / efficiency	[100%] [75%] [50%]	83,5 82,9 79,9
Schutzart / degree of protection	[IP]	IP55
Drehmoment / torque	[Nm]	39,8
Betriebsart / type of duty		S1
Iso.Kl		≤95
max. Temperaturanstieg / temperature rise	[K]	≤75
Frequenz / frequency	[Hz]	50/60
Spannung / voltage	230/400 [Δ/Y] 50Hz 265/460 [Δ/Y] 60Hz	
Motorschutz / motor protection	3xPTC Kaltleiter	
Herstellungsjahr production year	siehe Seriennummer 1. vier Stellen see serial number 1. four digits	

Anzugs- zu Nennstrom / starting current	[Ia/In]	6,5
Kipp- zu Nennmoment / pull-out torque	[MK/Mn]	2,2
Anzugs- zu Nennmoment / starting torque	[Ma/Mn]	1,8
Trägheitsmoment / moment of inertia	[Kgm ²]	0,04060
Lager / bearing	[DE] [NDE]	6308 6308
max. Radialbelastung / max. radial force	[N]	295,798
SchalleLeistungspegel / noise level	[dB]	69
Umgebungstemperatur / ambient temperature	[°C]	≤40
Gewicht / weight	[kg]	0
Aufstellungshöhe altitude	[m]	≤1000